



**THE FUTURE IS HERE
& IT'S BRIGHT**



LED PRODUCT CATALOGUE



Let's illuminate

At the heart of our operations is a steadfast commitment to quality and innovation in the LED industry. We take pride in manufacturing and supplying a diverse range of LED products tailored to meet the evolving needs of the Singapore market. Our focus on energy efficiency and sustainability not only enhances the environments we illuminate but also contributes to a greener future. With a dedication to exceptional customer service and cutting-edge technology, we strive to provide lighting solutions that elevate spaces while ensuring reliability and performance. Join us on our journey to light up Singapore with brilliance and efficiency!



K&N Enterprise



+65 9299 9332



info@nahvibiz.com



www.kambals.hk



10 Jalan Besar #08-05 Sim Lim Tower 208787 , Singapore.

LED BULB SERIES



B101



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/cdn
3W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	530*285*195	100
5W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	580*290*230	100
7W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	630*315*240	100
9W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	630*315*240	100
12W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	630*315*260	100
12W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	630*315*260	100
15W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	365*365*290	50
18W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	420*420*310	50
24W	AC165-265V	3000-6500K	E27/B22	25000	70-95lm/w	495*495*365	50



B102



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
3W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	530*265*195	130
5W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	580*295*230	130
7W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	630*315*240	130
9W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	630*315*240	130
12W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	630*315*260	130
12W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	630*315*260	130
15W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	365*365*290	50
18W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	420*420*310	50
24W	AC105-265V	3000-6500K	E27/B22	25000	70-95lm/w	485*485*365	50

B103



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
5W	AC105-265V	3000-6500K	E27/B22	25000	70-80lm/w	520*265*205	100
10W	AC105-265V	3000-6500K	E27/B22	25000	70-80lm/w	630*315*240	100
15W	AC105-265V	3000-6500K	E27/B22	25000	70-80lm/w	730*365*265	100
20W	AC105-265V	3000-6500K	E27/B22	25000	70-80lm/w	830*415*300	100
30W	AC105-265V	3000-6500K	E27/B22	25000	70-80lm/w	515*515*360	50
40W	AC105-265V	3000-6500K	E27/B22	25000	70-80lm/w	580*580*420	50
50W	AC105-265V	3000-6500K	E27/B22	25000	70-80lm/w	620*620*450	50
60W	AC105-265V	3000-6500K	E27/B22	25000	70-80lm/w	695*695*480	50

B104



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
5W	AC105-265V	3000-6500K	E27/B22	25000	85-90lm/w	520*265*205	130
10W	AC105-265V	3000-6500K	E27/B22	25000	85-90lm/w	630*315*240	130
15W	AC105-265V	3000-6500K	E27/B22	25000	85-90lm/w	730*365*265	130
20W	AC105-265V	3000-6500K	E27/B22	25000	85-90lm/w	830*415*300	130
30W	AC105-265V	3000-6500K	E27/B22	25000	85-90lm/w	515*515*360	50
40W	AC105-265V	3000-6500K	E27/B22	25000	85-90lm/w	580*580*420	50
50W	AC105-265V	3000-6500K	E27/B22	25000	85-90lm/w	620*620*450	50
60W	AC105-265V	3000-6500K	E27/B22	25000	85-90lm/w	695*695*480	50

B105



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
5W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	520*265*205	130
10W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	630*315*240	130
15W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	730*365*265	130
20W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	830*415*300	130
30W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	515*515*360	50
40W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	580*580*420	50
50W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	620*620*450	50
60W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	695*695*480	50
80W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w	720*435*480	30
100W	AC105-265V	3000-6500K	E27/B22	25000	90lm/w		



B106



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
5W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	520*285*205	100
10W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	630*315*240	100
15W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	730*365*265	100
20W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	830*415*300	100
30W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	515*515*360	50
40W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	580*580*420	50
50W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	620*620*450	50
60W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	695*695*480	50
80W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	720*435*480	30

B107



Watts	Voltage	Diameter (mm)	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
20W	AC165-265V	φ65	3000-6500K	E27/B22	25000	80lm/w	680*340*335	100
30W	AC165-265V	φ90	3000-6500K	E27/B22	25000	80lm/w	475*475*480	50
40W	AC165-265V	φ105	3000-6500K	E27/B22	25000	80lm/w	550*550*500	50
60W	AC165-265V	φ120	3000-6500K	E27/B22	25000	80lm/w	625*625*580	30
105W	AC165-265V	Φ140	3000-6500K	E27/B22	25000	80lm/w		

B108



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
3W	AC165-265V	3000-6500K	E14/E27	25000	90lm/w	420*420*162	200
7W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	530*265*190	100
9W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	660*330*230	100
12W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	800*415*250	100

B109



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
5W	A165-265V	3000-6500K	E27/B22/E14	25000	90lm/w	350*175*220	100
7W	A165-265V	3000-6500K	E27/B22/E14	25000	90lm/w	400*265*250	100
9W	A165-265V	3000-6500K	E27/B22/E14	25000	90lm/w	400*265*260	100
12W	A165-265V	3000-6500K	E27/B22/E14	25000	90lm/w	470*235*300	100
15W	A165-265V	3000-6500K	E27/B22/E14	25000	90lm/w	470*235*300	100
18W	A165-265V	3000-6500K	E27/B22/E14	25000	90lm/w	520*265*310	100

B110



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ch
24W	AC165-265V	3000-6500K	E27	25000	80lm/w	630×360×270	50
36W	AC165-265V	3000-6500K	E27	25000	80lm/w	430×430×510	50
48W	AC165-265V	3000-6500K	F27	25000	80lm/w	590×590×380	50

B111



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ch
24W	AC165-265V	3000-6500K	E27	25000	80lm/w	630×360×270	50
36W	AC165-265V	3000-6500K	E27	25000	80lm/w	430×430×510	50
48W	AC165-265V	3000-6500K	E27	25000	80lm/w	590×590×380	50

B112



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ch
60W(4+1)	AC165-265V	3000-6500K	E27	25000	80lm/w	650×520×384	50
75W(5+1)	AC165-265V	3000-6500K	E27	25000	80lm/w		50
75W(5+1)	AC165-265V	3000-6500K	E27	25000	80lm/w		50
80W(3+1)	AC165-265V	3000-6500K	E27	25000	80lm/w		50

B113



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ch
18W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	550×510×235	50
24W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	730×540×290	50
36W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	485×390×390	20
50W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	475×460×460	20



B114



Watts	Voltage	Color Temp	Size (mm)	Packing pcs/ctn
24W LAMP+4W TAN	AC165-265V	6500K	206x110	
30W LAMP+4W TAN	AC165-265V	6500K	206x110	

B115



Watts	Voltage	Diameter (mm)	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
22W	AC165-265V	φ65	3000-6500K	E27/B22	25000	80lm/w	680×340×335	100
35W	AC165-265V	φ90	3000-6500K	E27/B22	25000	80lm/w	475×475×450	50
45W	AC165-265V	φ105	3000-6500K	E27/B22	25000	80lm/w	550×550×500	50
55W	AC165-265V	φ120	3000-6500K	E27/B22	25000	80lm/w	625×625×580	30

B116



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
80W	AC165-265V	3000-6500K	E14/E27	25000	90lm/w	680×340×335	100
100W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	475×475×450	50
150W	AC165-265V	3000-6500K	E27/B22	25000	90lm/w	550×550×500	50

B117



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing position
-------	---------	------------	-------------	---------	-----------------	-------------------	------------------



B118



BM01



Watts	Voltage	Color Temp	Socket Type	Life(h)	Emergency Time	Battery Capacity (mAh)	Packing Size (mm)	Packing pcs/cdn
7W	AC185-265V	3000-6500K	E27	25000	2 Hours	1200	320*320*240	50
9W	AC185-265V	3000-6500K	E27	25000	2 Hours	1500	365*365*290	50
12W	AC185-265V	3000-6500K	E27	25000	2 Hours	2000	420*420*310	50
15W	AC185-265V	3000-6500K	E27	25000	2 Hours	2500	485*485*365	50
18W	AC185-265V	3000-6500K	E27	25000	2 Hours	2*1500	485*485*365	50
9W	AC185-265V	3000-6500K	E27	25000	2 Hours	1200	365*365*290	50
12W	AC185-265V	3000-6500K	E27	25000	2 Hours	1200	405*405*320	50

BM02



Watts	Voltage	Color Temp	Socket Type	Life(h)	Emergency Time	Battery Capacity (mAh)	Packing Size (mm)	Packing pcs/cdn
7W	AC185-265V	3000-6500K	E27	25000	2 Hours	1200	320*320*240	50
9W	AC185-265V	3000-6500K	E27	25000	2 Hours	1500	320*320*260	50
20W	AC185-265V	3000-6500K	E27	25000	2 Hours	2*1200	415*415*340	50

BM03



Watts	Voltage	Color Temp	Socket Type	Life(h)	Emergency Time	Battery Capacity (mAh)	Packing Size (mm)	Packing pcs/cdn
12W	AC185-265V	3000-6500K	E27	25000	2 Hours	1500	370*370*310	50
15W	AC185-265V	3000-6500K	E27	25000	2 Hours	2*1200	415*415*340	50
20W	AC185-265V	3000-6500K	E27	25000	2 Hours	3*1200	480*480*390	50

BM04



Watts	Voltage	Color Temp	Socket Type	Life(h)	Emergency Time	Battery Capacity (mAh)	Packing Size (mm)	Packing pcs/cdn
7W	AC185-265V	3000-6500K	E27	25000	2 Hours	1200	320*320*240	50
9W	AC185-265V	3000-6500K	E27	25000	2 Hours	1500	365*365*290	50
12W	AC185-265V	3000-6500K	E27	25000	2 Hours	2000	420*420*310	50
15W	AC185-265V	3000-6500K	E27	25000	2 Hours	2500	485*485*365	50
18W	AC185-265V	3000-6500K	E27	25000	2 Hours	2*1500	485*485*365	50

BD01



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
3W	DC12-80V	3000-6500K	E27/B22	25000	90lm/w	530*265*195	100
5W	DC12-80V	3000-6500K	E27/B22	25000	90lm/w	580*290*220	100
7W	DC12-80V	3000-6500K	E27/B22	25000	90lm/w	630*315*240	100
9W	DC12-80V	3000-6500K	E27/B22	25000	90lm/w	630*315*240	100
12W	DC12-80V	3000-6500K	E27/B22	25000	90lm/w	680*340*270	100

BD02



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
3W	DC12V/24V	3000-6500K	E27/B22	25000	90lm/w	530*265*195	100
5W	DC12V/24V	3000-6500K	E27/B22	25000	90lm/w	580*290*220	100
7W	DC12V/24V	3000-6500K	E27/B22	25000	90lm/w	630*315*240	100
9W	DC12V/24V	3000-6500K	E27/B22	25000	90lm/w	630*315*240	100
12W	DC12V/24V	3000-6500K	E27/B22	25000	90lm/w	680*340*270	100
15W	DC12V/24V	3000-6500K	E27/B22	25000	90lm/w	365*365*290	50
18W	DC12V/24V	3000-6500K	E27/B22	25000	90lm/w	420*420*320	50
24W	DC12V/24V	3000-6500K	E27/B22	25000	90lm/w	490*490*380	50

BD03



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
1W-Clear cover	DC12/24	3000-6500K	E27/B22	25000	90lm/w		100
2W-Clear cover	DC12/24	3000-6500K	E27/B22	25000	90lm/w		100
3W-Clear cover	DC12/24	3000-6500K	E27/B22	25000	90lm/w		100
1W-Frosted cover	DC12/24	3000-6500K	E27/B22	25000	90lm/w		100
2W-Frosted cover	DC12/24	3000-6500K	E27/B22	25000	90lm/w		50
3W-Frosted cover	DC12/24	3000-6500K	E27/B22	25000	90lm/w		50

BD04



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
5W	DC12V	3000-6500K	E27/B22	25000	70lm/w	520*265*295	100
9W	DC12V	3000-6500K	E27/B22	25000	70lm/w	630*315*240	100
15W	DC12V	3000-6500K	E27/B22	25000	70lm/w	730*365*265	100
20W	DC12V	3000-6500K	E27/B22	25000	70lm/w	830*415*300	100
25W	DC12V	3000-6500K	E27/B22	25000	70lm/w	515*515*360	50



BD05



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
1W Green body	DC12V	3000-6500K	E27/B22	25000	70lm/w	530X265X220	100
1W Red body	DC12V	3000-6500K	E27/B22	25000	70lm/w	630X315X240	100

BD06



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
12W	220V	3000/6500K	E27/B22	25000	80lm/w	420×220×260	100
12W	220V	CHANGE COLOR	E27/B22	25000	80lm/w	420×220×260	100
16W	220V	3000/6500K	E27/B22	25000	80lm/w	420×220×260	100
16W	220V	CHANGE COLOR	E27/B22	25000	80lm/w	420×220×260	100

BD07



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
T50-1W	DC12V	3000/6500K	E27-B22	25000	80lm/w	730X355X285	100
T60-2W	DC12V	3000/6500K	E27-B22	25000	80lm/w	730X355X285	100
T70-3W	DC12V	3000/6500K	E27-B22	25000	80lm/w	830X415X330	100

BD08



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
14W	85-265V	3000/6500K	E14/E27	25000	80lm/w	565X288X238	100
14W	85-265V	CHANGE COLOR	E14/E27	25000	80lm/w	565X288X238	100
16W	85-265V	3000/6500K	E14/E27	25000	80lm/w	565X288X238	100
16W	85-265V	CHANGE COLOR	E14/E27	25000	80lm/w	565X288X238	100
12+12W	85-265V	3000/6500K	E14/E27	25000	80lm/w	565X288X238	100
12+12W	85-265V	CHANGE COLOR	E14/E27	25000	80lm/w	565X288X238	100



BD09



Watts	Voltage	Color Temp	Socket Type	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
5W	85-265V	3000K/5000K	E14/E27	25000	80lm/w	480X180X290	100
9W	85-265V	CHANGE COLOR	E14/E27	25000	80lm/w	480X180X290	100
7W	85-265V	3000K/5000K	E14/E27	25000	80lm/w	480X180X290	100
7W	85-265V	CHANGE COLOR	E14/E27	25000	80lm/w	480X180X290	100
9W	85-265V	3000K/5000K	E14/E27	25000	80lm/w	480X180X290	100
9W	85-265V	CHANGE COLOR	E14/E27	25000	80lm/w	480X180X290	100

BD10



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
30W	DC12-80V	3000K/5000K	25000	80lm/w		
50W	DC12-80V	3000K/5000K	25000	80lm/w		




S501



Watts	Color Temp.	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/cdn
200W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)		3
300W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)		3

S502



Watts	Color Temp.	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/cdn
50W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1
100W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1
150W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1
200W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1
300W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1

S503



Watts	Color Temp.	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/cdn
50W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1
100W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1
150W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1
200W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1
300W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)	610*410*170	1

S504



Watts	Color Temp.	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/cdn
400W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)		1
500W	3000-6500K	Aluminum+Glass	IP67	5-8H	12H(optional)		1

S505



Watts	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/ctn
200W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	540*430*390	4
300W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	540*430*390	4
400W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	540*430*390	4

S506



Watts	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/ctn
50W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	510*450*155	1
80W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	510*450*155	1
100W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	580*410*170	1
200W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	610*410*170	1
300W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	610*410*170	1
400W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	710*480*170	1
500W	Aluminium+Glass	IP67	5-8Hours	12H(optional)	710*540*250	1

S507



Watts	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/ctn
100W	Aluminium+Glass	IP66	5-8Hours			1
200W	Aluminium+Glass	IP66	5-8Hours			1
300W	Aluminium+Glass	IP66	5-8Hours			1
400W	Aluminium+Glass	IP66	5-8Hours			1
500W	Aluminium+Glass	IP66	5-8Hours			1

S508A




Watts	Material	Battery Capacity(mAh)	Packing Size (mm)	Packing pcs/ctn
1W / 5V ROUND	ABS	1200	850*850*365	10
1W / 5V SQUARE	ABS	1200	850*850*365	10
1W / 5V TRIANGULAR	ABS	1200	935*850*365	10
1W / 5V HEXAGONAL	ABS	1200	935*850*365	10

S508B



Watts	COLOR	Material	Battery Capacity(mAh)	Packing Size (mm)	Packing pcs/ctn
1W / 5V	RGB	ABS	1200	850*385*235	10
2W / 3.7V	RGB	ABS	1200	850*385*235	10

S509



Watts	Number of lamp beads	Battery Capacity(mAh)	Packing Size (mm)	Packing pcs/ctn
20W	235pcs 5730	8000	645*380*710	10
40W	235pcs 5730	13000	645*380*710	10
60W	235pcs 5730	15000	520*390*745	8
100W	350pcs 5730	18000	520*390*745	8
150W	350pcs 5730	20000	775*380*685	6
200W	350pcs 5730	25000	775*380*685	6

S510



Watts	Function	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/ctn
50W	Radar sensor	Aluminum	IP67	5-8hours	12h(optional)	790*780*300	6
100W	Radar sensor	Aluminum	IP67	5-8hours	12h(optional)	850*850*300	6
150W	Radar sensor	Aluminum	IP67	5-8hours	12h(optional)	1020*490*290	3
200W	Radar sensor	Aluminum	IP67	5-8hours	12h(optional)	1270*490*290	3

S511



Watts	Function	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/ctn
50W	Radar sensor	Aluminum	IP67	5-8hours	12h(optional)	905*225*455	1
100W	Radar sensor	Aluminum	IP67	5-8hours	12h(optional)	755*225*455	1
150W	Radar sensor	Aluminum	IP67	5-8hours	12h(optional)	955*225*455	1

S512



Watts	Function	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/cdn
120W	Radar sensor	ABS	IP67	5-8hours	12H(optional)	535×370×650	10
200W	Radar sensor	ABS	IP67	5-8hours	12H(optional)	575×370×750	10
300W	Radar sensor	ABS	IP67	5-8hours	12H(optional)	645×305×525	10

S513



Watts	Function	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/cdn
50W	Radar sensor	ABS	IP67	5-8hours	12H(optional)		10
100W	Radar sensor	ABS	IP67	5-8hours	12H(optional)		10
150W	Radar sensor	ABS	IP67	5-8hours	12H(optional)		5

S514



Watts	Function	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/cdn
30W	Radar sensor	ABS	IP67	5-8hours	12H(optional)		40
50W	Radar sensor	ABS	IP67	5-8hours	12H(optional)		10
100W	Radar sensor	ABS	IP67	5-8hours	12H(optional)		10
150W	Radar sensor	ABS	IP67	5-8hours	12H(optional)		5
200W	Radar sensor	ABS	IP67	5-8hours	12H(optional)		5

S515



Watts	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/cdn
600W	ABS	IP67	5-8hours	12H(optional)		5
1200W	ABS	IP67	5-8hours	12H(optional)		4
1800W	ABS	IP67	5-8hours	12H(optional)		4

SOLAR LIGHT



Watts	Function	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/ctn
30W	Radar sensor	ABS	IP67	5-8Hours	12H(optional)		10
60W	Radar sensor	ABS	IP67	5-8Hours	12H(optional)		5
90W	Radar sensor	ABS	IP67	5-8Hours	12H(optional)		5
120W	Radar sensor	ABS	IP67	5-8Hours	12H(optional)		5

SOLAR LIGHT



Watts	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/ctn
30W	ABS	IP67	5-8hours	12H(optional)		10
60W	ABS	IP67	5-8hours	12H(optional)		10
90W	ABS	IP67	5-8hours	12H(optional)		10
120W	ABS	IP67	5-8hours	12H(optional)		5

SOLAR LIGHT



Watts	Material	Protection grade	Charging Time(H)	Working Time(H)	Packing Size (mm)	Packing pcs/ctn
180W	ABS	IP67	5-8hours	12H(optional)		10
200W	ABS	IP67	5-8hours	12H(optional)		10

SOLAR LIGHT



Watts	Material	Protection grade	Battery	Solar Panel	Packing Size (mm)	Packing pcs/ctn
200W	ABS	IP67	3.2V 15AH	6V 18W	536X398X80	1
300W	ABS	IP67	3.2V 20AH	6V 25W	680X398X80	1
400W	ABS	IP67	3.2V 25AH	6V 30W	765X398X80	1

BS01A



Watts	Color Temp	Material	Charging Voltage	Powered By	Packing Size (mm)	Packing position	Work Time (h)
50W	6500K	Plastic	5V	Solar lithium battery	375×385×475	20	10-12

BS01B



Watts	Color Temp	Material	Charging Voltage	Powered By	Packing Size (mm)	Packing position
100W	6500K	Plastic	5V	Solar lithium battery	370×360×480	20
150W	6500K	Plastic	5V	Solar lithium battery	370×360×480	20

BS02



Watts	Color Temp	Material	Charging Voltage	Battery	Packing Size (mm)	Packing position
100W	6500K	Plastic	5V	2X1200mAh	340X270X35	40

BS03




Watts	Color Temp	Material	Charging Voltage	Battery	Packing Size (mm)	Packing position
200W	6500K	Plastic	5V	2X1200mAh	600X290X35	30

BS04



Watts	Color Temp	Material	Charging Voltage	Battery	Packing Size (mm)	Packing pcs/ctn
500W	6500K	Plastic	6V	4X1200mAh	640X640X30	20

BS05



Watts	Color Temp	Material	Charging Voltage	Battery	Packing Size (mm)	Packing pcs/ctn
1000W	6500K	Plastic	6V	6X1200mAh	480X380X35	10

BS06



Watts	Color Temp	Material	Charging Voltage	Battery	Packing Size (mm)	Packing pcs/ctn
200W	6500K	Plastic	6V	3X1200mAh	660X320X340	40

BS07



Watts	Color Temp	Material	Battery	Packing Size (mm)	Packing pcs/ctn
200W	6500K	Plastic	4X1200mAh	600X260X350	30
500W	6500K	Plastic	6X1200mAh	640X240X380	20




BS08



Watts	Color Temp	Battery Capacity(mAh)	Socket Type
20W	6500K	1200	DC3.5
30W	6500K	2*1200	DC3.5
40W	6500K	3*1200	DC3.5
6V/2.5W			
6V/4.5W			
6V/6W			
6V/8W	350°235°17mm		
6V/10W	350°235°17mm		

BS09



Watts	Color Temp	Material	Protection grade	Beam Angle	Packing Size (mm)	Packing pcs/cdn	Work Time (H)
100W	3000-6500K	Aluminum+PC	IP67	90°	595*375*265	10	12
200W	3000-6500K	Aluminum+PC	IP67	90°	675*375*375	8	12
300W	3000-6500K	Aluminum+PC	IP67	90°	675*360*375	6	12
400W	3000-6500K	Aluminum+PC	IP67	90°	625*280*380	4	12

BS10



Watts	Color Temp	Material	Protection grade	Function	Packing Size (mm)	Packing pcs/cdn	Work Time (H)
25W	3000-6500K	ABS plastic	IP67	Remote	520*360*225	20	12
40W	3000-6500K	ABS plastic	IP67	Remote	520*440*255	20	12
60W	3000-6500K	ABS plastic	IP67	Remote	480*365*280	10	12
100W	3000-6500K	ABS plastic	IP67	Remote	420*330*555	10	12
200W	3000-6500K	ABS plastic	IP67	Remote	450*315*370	5	12
300W	3000-6500K	ABS plastic	IP67	Remote			12

BS11




Watts	Color Temp	Material	Protection grade	Function	Packing Size (mm)	Packing pcs/cdn	Work Time (H)
25W	3000-6500K	Aluminum	IP67	Remote	520*360*225	20	12
40W	3000-6500K	Aluminum	IP67	Remote	520*440*255	20	12
60W	3000-6500K	Aluminum	IP67	Remote	480*365*280	10	12
100W	3000-6500K	Aluminum	IP67	Remote	420*330*555	10	12
200W	3000-6500K	Aluminum	IP67	Remote	450*315*370	5	12
300W	3000-6500K	Aluminum	IP67	Remote	550*380*450	5	12

BS12



Watts	Color Temp	Material	Protection grade	Function	Packing Size (mm)	Packing pos/cdn	Work Time (H)
50W	3000-6500K	Aluminum	IP67	Remote	470*375*480	8	12
70W	3000-6500K	Aluminum	IP67	Remote	470*375*480	8	12
120W	3000-6500K	Aluminum	IP67	Remote	430*375*620	6	12
200W	3000-6500K	Aluminum	IP67	Remote	430*375*620	6	12

BS13



Watts	Color Temp	Material	Protection grade	Battery Capacity (mAh)	Function	Packing Size (mm)	Packing pos/cdn	Work Time (H)
100W	3000-6500K	Aluminum	IP67	6000	Remote	740*420*265	10	12
160W	3000-6500K	Aluminum	IP67	12000	Remote	450*370*520	10	12
200W	3000-6500K	Aluminum	IP67	18000	Remote	535*370*380	6	12
300W	3000-6500K	Aluminum	IP67	24000	Remote	555*550*380	6	12
400W	3000-6500K	Aluminum	IP67	30000	Remote	620*455*380	5	12
600W	3000-6500K	Aluminum	IP67	36000	Remote	620*455*380	4	12

BS14




Watts	Color Temp	Material	Battery Capacity (mAh)	Emergency Time (H)	Packing Size (mm)	Packing pos/cdn
10W	3000-6500K	Aluminum	2200	4	565*275*470	20
20W	3000-6500K	Aluminum	2200	4	615*355*290	10
30W	3000-6500K	Aluminum	2200	4	475*420*375	6
50W	3000-6500K	Aluminum	2200	4	475*420*375	4

BS15



Lamp (mm)	Color Temp	Solar Panel	Protection grade	Battery Capacity	Packing Size (mm)	Packing pos/cdn
4*610*180	6000-6500K	5V 20W	IP65	3.2V 35AH	625X620X130	

BS16



Watts	Color Temp	Material	Protection grade	Solar Panel	Packing Size (mm)	Packing pos/cn	Work Time (H)
100W	3000-6500K	Aluminum	IP67	6V60W		10	12
300W	3000-6500K	Aluminum	IP67	6V80W		8	12
300W	3000-6500K	Aluminum	IP67	6V12W		8	12
400W	3000-6500K	Aluminum	IP67	6V15W		6	12
500W	3000-6500K	Aluminum	IP67	6V20W		6	12

BS17



Watts	Color Temp	Material	Protection grade	Solar Panel	Packing Size (mm)	Packing pos/cn	Work Time (H)
60W	3000-6500K	Aluminum+PC	IP67	6V6W		10	12
100W	3000-6500K	Aluminum+PC	IP67	6V8W		8	12
200W	3000-6500K	Aluminum+PC	IP67	6V12W		8	12
300W	3000-6500K	Aluminum+PC	IP67	6V15W		6	12

BS18



Watts	Color Temp	Material	Protection grade	Function	Packing Size (mm)	Packing pos/cn	Work Time (H)
60W	3000-6500K	Aluminum+PC	IP67	Remote		10	12
100W	3000-6500K	Aluminum+PC	IP67	Remote		8	12
200W	3000-6500K	Aluminum+PC	IP67	Remote		8	12
300W	3000-6500K	Aluminum+PC	IP67	Remote		6	12
400W	3000-6500K	Aluminum+PC	IP67	Remote		6	12

BS19



Watts	Color Temp	Material	Protection grade	Solar Panel	Packing Size (mm)	Packing pos/cn	Work Time (H)
50W	3000-6500K	Aluminum	IP67	6V6W	360*330*210		12
100W	3000-6500K	Aluminum	IP67	6V8W	440*380*290		12
150W	3000-6500K	Aluminum	IP67	6V12W	440*320*380		12
200W	3000-6500K	Aluminum	IP67	6V15W	480*280*380		12

BS20



Solar Panel Watts	Voltage	LED Bulb PCs	Socket Type	Protection grade	Packing Size (mm)	Packing pcs/ctn
2W	220-240V	15	E27/E22	IP65	520*505*405	12

BS21




Watts	Protection grade	Solar Panel	Packing Size (mm)	Packing pcs/ctn
10W	IP65	5.5V 0.55W	68X53X37	50

BS22



Watts	Color Temp.	Protection grade	Packing Size (mm)	Packing pcs/ctn	Work Time (h)
40W	3000-6500K	IP67	356X342X225	12	20
60W	3000-6500K	IP67	440X356X260	12	20
120W	3000-6500K	IP67	484X356X285	12	20
200W	3000-6500K	IP67	680X356X293	12	20
300W	3000-6500K	IP67	760X356X330	12	20
400W	3000-6500K	IP67	415X355X356	6	20

BS23




Watts	Color Temp.	Protection grade	Packing Size (mm)	Packing pcs/ctn	Work Time (h)
60W	3000-6500K	IP67			20
100W	3000-6500K	IP67			20
200W	3000-6500K	IP67			20
300W	3000-6500K	IP67			20

BS24



Watts	Color Temp.	Protection grade	Packing Size (mm)	Packing pcs/ctn	Work Time (h)
60W	3000-6500K	IP67			20
100W	3000-6500K	IP67			20
150W	3000-6500K	IP67			20
200W	3000-6500K	IP67			20



D720



Watts	Voltage	Color Temp.	Dimension (mm)	Cut Hole Size open (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
7W	AC85-265V	3000-6500K	φ88×50	φ75	25000	70lm/w	520×295×425	100
10W	AC85-265V	3000-6500K	φ127×58	φ100	25000	70lm/w	695×270×290	50
15W	AC85-265V	3000-6500K	φ160×58	φ140	25000	70lm/w	525×375×380	40
20W	AC85-265V	3000-6500K	φ190×58	φ175	25000	70lm/w	410×320×415	20
30W	AC85-265V	3000-6500K	φ220×58	φ200	25000	70lm/w	465×295×490	20

D721



Watts	Voltage	Color Temp.	Dimension (mm)	Cut Hole Size open (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
7W	AC85-265V	3000-6500K	φ88×50	φ75	25000	70lm/w	490×290×410	100
10W	AC85-265V	3000-6500K	φ160×50	φ140	25000	70lm/w	570×355×360	40
30W	AC85-265V	3000-6500K	φ220×55	φ200	25000	70lm/w	465×315×470	20

D722




Watts	Voltage	Color Temp	Cut Hole Size open(mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
7W	AC85-265V	3000-6500K	φ70	25000	80lm/w	520*295*425	100
15W	AC85-265V	3000-6500K	φ100	25000	80lm/w	695*270*290	50
15W	AC85-265V	3000-6500K	φ140	25000	80lm/w	525*375*380	40
20W	AC85-265V	3000-6500K	φ175	25000	80lm/w	410*320*415	20
30W	AC85-265V	3000-6500K	φ200	25000	80lm/w	485*295*490	20
60W	AC85-265V	3000-6500K	φ280	25000	80lm/w	650*490*260	10
80W	AC85-265V	3000-6500K	φ280	25000	80lm/w	650*490*260	10

D723



Watts	Voltage	Color Temp	Cut Hole Size open(mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
3W	AC85-265V	3000-6500K	φ200	25000	80lm/w	270X270X300	100
6W	AC85-265V	3000-6500K	φ200	25000	80lm/w	325X320X150	100

D724



Watts	Voltage	Color Temp	Dimension (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
20W	AC175-265V	3000-6500K	φ160*160	25000	75lm/w	520*385*365	40
30W	AC175-265V	3000-6500K	φ220*220	25000	75lm/w	470*270*470	20
40W	AC175-265V	3000-6500K	φ300*300	25000	75lm/w	500*320*335	10

PR701



Watts	Voltage	Color Temp	Dimension (mm)	Cut Hole Size open(mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
3W	AC100-265V	3000-6500K	φ83	φ70	25000	60-75lm/w	610*300*295	100
6W	AC100-265V	3000-6500K	φ115	φ105	25000	60-75lm/w	630*310*305	100
9W	AC100-265V	3000-6500K	φ140	φ130	25000	60-75lm/w	365*300*425	40
12W	AC100-265V	3000-6500K	φ160	φ155	25000	60-75lm/w	365*300*425	40
18W	AC100-265V	3000-6500K	φ220	φ205	25000	60-75lm/w	460*310*270	20
24W	AC100-265V	3000-6500K	φ295	φ285	25000	60-75lm/w	615*300*340	20

PS701



Watts	Voltage	Color Temp.	Dimension (mm)	Cut Hole Size open(mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
3W	AC100-265V	3000-6500K	φ65	φ70	25000	60-75lm/w	610×380×205	180
6W	AC100-265V	3000-6500K	φ115	φ120	25000	60-75lm/w	630×310×305	180
9W	AC100-265V	3000-6500K	φ140	φ130	25000	60-75lm/w	365×320×425	40
12W	AC100-265V	3000-6500K	φ160	φ155	25000	60-75lm/w	365×390×425	40
18W	AC100-265V	3000-6500K	φ220	φ255	25000	60-75lm/w	465×310×270	20
24W	AC100-265V	3000-6500K	φ295	φ285	25000	60-75lm/w	615×380×340	20

PR702



Watts	Voltage	Color Temp.	Dimension (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
6W	AC100-265V	3000-6500K	φ120	25000	60-75lm/w	620×340×260	180
12W	AC100-265V	3000-6500K	φ175	25000	60-75lm/w	360×340×360	40
18W	AC100-265V	3000-6500K	φ225	25000	60-75lm/w	460×340×235	20
24W	AC100-265V	3000-6500K	φ300	25000	60-75lm/w	610×340×310	20

PS702



Watts	Voltage	Color Temp.	Dimension (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
6W	AC100-265V	3000-6500K	120×120	25000	60-75lm/w	620×340×260	180
12W	AC100-265V	3000-6500K	175×175	25000	60-75lm/w	360×340×360	40
18W	AC100-265V	3000-6500K	225×225	25000	60-75lm/w	460×340×235	20
24W	AC100-265V	3000-6500K	300×300	25000	60-75lm/w	610×340×310	20

PR703



Watts	Voltage	Color Temp.	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
10W	AC180-265V	3000-6500K	25000	90-100lm/w	555×348×285	180
18W	AC180-265V	3000-6500K	25000	90-100lm/w	655×348×325	180
24W	AC180-265V	3000-6500K	25000	90-100lm/w	370×348×430	40
36W	AC180-265V	3000-6500K	25000	90-100lm/w	470×348×425	40

PS703



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/cn
10W	AC100-265V	3000-6500K	25000	90-100lm/w	555*340*285	100
18W	AC100-265V	3000-6500K	25000	90-100lm/w	655*340*325	100
24W	AC100-265V	3000-6500K	25000	90-100lm/w	370*340*430	40
36W	AC100-265V	3000-6500K	25000	90-100lm/w	470*340*425	40

PRS704



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/cn
18W	AC100-265V	3000-6500K	25000	90-100lm/w	540*270*270	40
24W	AC100-265V	3000-6500K	25000	90-100lm/w	540*370*370	40
36W	AC100-265V	3000-6500K	25000	90-100lm/w	540*475*245	20

PSS704




Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/cn
6W	AC100-265V	6500K	25000	90-100lm/w		
9W	AC100-265V	6500K	25000	90-100lm/w		
12W	AC100-265V	6500K	25000	90-100lm/w		
18W	AC100-265V	6500K	25000	90-100lm/w		
24W	AC100-265V	6500K	25000	90-100lm/w		

PSS705



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/cn
3W	AC100-265V	6500K	25000	90-100lm/w		
5W	AC100-265V	6500K	25000	90-100lm/w		
7W	AC100-265V	6500K	25000	90-100lm/w		

P706



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
6-6W	AC100-265V	3000K-4000K-6500K	25000	90-100lm/w		
9-9W	AC100-265V	3000K-4000K-6500K	25000	90-100lm/w		
12-12W	AC100-265V	3000K-4000K-6500K	25000	90-100lm/w		
18-18W	AC100-265V	3000K-4000K-6500K	25000	90-100lm/w		
24-24W	AC100-265V	3000K-4000K-6500K	25000	90-100lm/w		

P707



Watts	Voltage	Color Temp	Dimension (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
6W	AC165-265V	3000-6500K	φ70	25000	90lm/w	670×240×420	100
12W	AC165-265V	3000-6500K	φ120	25000	90lm/w	470×360×365	40
18W	AC165-265V	3000-6500K	φ160	25000	90lm/w	710×240×425	30
24W	AC165-265V	3000-6500K	φ200	25000	90lm/w	570×270×520	20
6-6W	AC165-265V	3000K-4000K-6500K	φ70	25000	90lm/w	670×240×420	100
12-12W	AC165-265V	3000K-4000K-6500K	φ120	25000	90lm/w	470×360×365	40
18-18W	AC165-265V	3000K-4000K-6500K	φ160	25000	90lm/w	710×240×425	30
24-24W	AC165-265V	3000K-4000K-6500K	φ200	25000	90lm/w	570×270×520	20

P708



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
6-6W	AC100-265V	WH+B/WW+B	25000	90-100lm/w		60
12-12W	AC100-265V	WH+B/WW+B	25000	90-100lm/w		40
18-18W	AC100-265V	WH+B/WW+B	25000	90-100lm/w		30
24-24W	AC100-265V	WH+B/WW+B	25000	90-100lm/w		20

PR709




Watts	Voltage	Color Temp	Dimension (mm)	Cut Hole Size open (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
3-3W	AC165-265V	WH+B/WW+B	105×105	75×75	25000	70lm/w	470×270×390	50
6-3W	AC165-265V	WH+B/WW+B	145×145	105×105	25000	70lm/w	480×340×340	40
12-0W	AC165-265V	WH+B/WW+B	195×195	155×155	25000	70lm/w	470×225×430	40
18-6W	AC165-265V	WH+B/WW+B	245×245	205×205	25000	70lm/w	470×270×520	20
24-12W	AC165-265V	WH+B/WW+B	305×305	285×285	25000	70lm/w	340×350×320	10



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
6+3W	AC165-265V	RGB	25000	70lm/w		
12+6W	AC165-265V	RGB	25000	70lm/w		
18+6W	AC165-265V	RGB	25000	70lm/w		
			25000	70lm/w		
			25000	70lm/w		

PPM709



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
6+3W	AC165-265V	RGB	25000	70lm/w		
12+6W	AC165-265V	RGB	25000	70lm/w		
18+6W	AC165-265V	RGB	25000	70lm/w		
			25000	70lm/w		
			25000	70lm/w		

DOWN LIGHT



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Cut Hole Size open(mm)	Packing Size (mm)	Packing pcs/cdn
40W	AC165-265V	3000-6500K	25000	95-105lm/w	595*595	630*630*320	10
48W	AC165-265V	3000-6500K	25000	95-105lm/w	595*595	630*630*320	10
54W	AC165-265V	3000-6500K	25000	95-105lm/w	595*595	630*630*320	10
64W	AC165-265V	3000-6500K	25000	95-105lm/w	595*595	630*630*320	10
72W	AC165-265V	3000-6500K	25000	95-105lm/w	595*595	630*630*320	10

DOWN LIGHT



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Cut Hole Size open(mm)	Packing Size (mm)	Packing pcs/cdn
40W	AC165-265V	3000-6500K	25000	95-105lm/w	600*600	670*670*340	10
48W	AC165-265V	3000-6500K	25000	95-105lm/w	600*600	670*670*340	10
54W	AC165-265V	3000-6500K	25000	95-105lm/w	600*600	670*670*340	10
64W	AC165-265V	3000-6500K	25000	95-105lm/w	600*600	670*670*340	10
72W	AC165-265V	3000-6500K	25000	95-105lm/w	600*600	670*670*340	10

P711



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
300×300-12W	AC165-265V	3000-6500K	25000	80lm/w	630×170×365	20
600×300-24W	AC165-265V	3000-6500K	25000	80lm/w	665×230×365	10
600×600-36W	AC165-265V	3000-6500K	25000	80lm/w	665×230×675	10
600×600-8-45W	AC165-265V	3000-6500K	25000	80lm/w	655×230×675	10
600×600-8-60W	AC165-265V	3000-6500K	25000	80lm/w	1275×230×365	10
1200×600-9-72W	AC165-265V	3000-6500K	25000	80lm/w	1280×230×665	5

P712



Watts	Voltage	Color Temp	Life(h)	Protection grade	Packing Size (mm)	Packing pcs/cdn
DWL01 24W	AC165-265V	3000-6500K	25000	IP65	355×345×430	20
DWL02 24W	AC165-265V	3000-6500K	25000	IP65	355×345×430	20
DWL03 24W	AC165-265V	3000-6500K	25000	IP65	355×345×430	20
DWL04 24W	AC165-265V	3000-6500K	25000	IP65	355×345×430	20

P713A



Watts	Voltage	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
18W-RD	AC165-265V	IP65	90lm/w	370×345×545	30
24W-RD	AC165-265V	IP65	90lm/w	460×395×660	20
30-RD	AC165-265V	IP65	90lm/w		20
18W-SQ	AC165-265V	IP65	90lm/w	440×345×380	30
24W-SQ	AC165-265V	IP65	90lm/w	560×395×320	20

P713B



Watts	Voltage	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
18W-RD	AC165-265V	IP65	90lm/w	370×345×545	30
24W-RD	AC165-265V	IP65	90lm/w	460×395×660	20
18W-SQ	AC165-265V	IP65	90lm/w	440×345×380	30
24W-SQ	AC165-265V	IP65	90lm/w	560×395×320	20

P713C



Watts	Voltage	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
24W-OVAL	AC165-265V	IP65	90lm/w		30
12+12W-OVAL	AC165-265V	IP65	90lm/w		20
24W-RD	AC165-265V	IP65	90lm/w		30
12+12W-RD	AC165-265V	IP65	90lm/w		20

P714



Watts	Voltage	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
15W-RD	AC165-240V	90lm/w	560×390×300	40
18W-RD	AC165-240V	90lm/w		40
25W-RD	AC165-240V	90lm/w	530×360×360	40
15W-OVAL	AC165-240V	90lm/w	310×305×370	40
18W-OVAL	AC165-240V			40
20W-OVAL	AC165-240V		440×330×450	40

P715



Watts	Voltage	Lamp Size (mm)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
12W-WH/WW	AC175-240V	116×375×260	90-100lm/w	365×245×275	20
12W-RGB	AC175-240V	116×375×260	90-100lm/w	365×245×275	12



P716



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
16W	AC100-265V	3000-6500K	25000	60-75lm/w	465×340×235	20
24W	AC100-265V	3000-6500K	25000	60-75lm/w	515×340×315	20

P717



Watts	Voltage	Color Temp	Life(h)	Dimension (mm)	Packing Size (mm)	Packing position
12W	AC165-265V	3000-6500K	25000	230	625*270*535	20
18W	AC165-265V	3000-6500K	25000	300	625*340*675	20
24W	AC165-265V	3000-6500K	25000	350	625*385*765	20

P718



Watts	Voltage	Color Temp	Life(h)	Protection grade	Dimension (mm)	Packing Size (mm)	Packing pos/cdn
25W	AC165-265V	3000K-6000K-6500K	25000	IP65	360	625*340*675	20

P719



Watts	Voltage	Protection grade	Color Temp	Packing Size (mm)	Packing position
24W	AC170-240V	IP65	W / WW		30
24W	AC170-240V	IP65	Change Color		20
24W	AC170-240V	IP65	W / WW		30
24W	AC170-240V	IP65	Change Color		20

P720



Watts	Voltage	Protection grade	Color Temp	Packing Size (mm)	Packing position
24W	AC170-240V	IP65	3000-6500K		20
24W	AC170-240V	IP65	3000-6500K		12



P721



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
9W	AC165-265V	3000-6500K	25000	90lm/w		
7W	AC165-265V	3000-6500K	25000	90lm/w		
5-58	AC165-265V	3000-6500K	25000	90lm/w		
7-78	AC165-265V	3000-6500K	25000	90lm/w		

P722




Watts	Voltage	Protection grade	Color Temp	Packing Size (mm)	Packing pcs/cn
2W	AC170-240V	IP65	3000-6500K		
4W	AC170-240V	IP65	3000-6500K		
6W	AC170-240V	IP65	3000-6500K		
8W	AC170-240V	IP65	3000-6500K		
10W	AC170-240V	IP65	3000-6500K		

P726



Watts	Voltage	Protection grade	Color Temp	Packing Size (mm)	Packing pcs/cn
5W-SQ	AC170-240V	IP65	3000-6500K	545X365X473	100
15W-SQ	AC170-240V	IP65	3000-6500K	570X575X380	50
5W-RD	AC170-240V	IP65	3000-6500K	570X575X380	100
15W-RD	AC170-240V	IP65	3000-6500K	545X365X473	30
15W	AC170-240V	IP65	3000-6500K	545X455X415	60
15W	AC170-240V	IP65	3000-6500K	545X455X415	60

P727



Watts	Voltage	Color Temp	Lighting Effect	Packing Size (mm)	Packing pcs/cn
60W	AC165-265V	3000-7000K	100lm/W	670X670X345	10

LED FLOOD SERIES



F800



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/cdn
10W	AC100-265V	RGB	Aluminum	IP65	25000	80m/w	330×285×575	100
20W	AC100-265V	RGB	Aluminum	IP65	25000	80m/w	480×330×435	90
30W	AC100-265V	RGB	Aluminum	IP65	25000	80m/w	345×330×455	60
50W	AC100-265V	RGB	Aluminum	IP65	25000	80m/w	405×330×370	40
100W	AC100-265V	RGB	Aluminum	IP65	25000	80m/w	485×485×220	30
150W	AC100-265V	RGB	Aluminum	IP65	25000	80m/w	525×480×230	30
200W	AC100-265V	RGB	Aluminum	IP65	25000	80m/w	490×330×245	15

F801



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/cdn
10W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	430×315×180	60
20W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	385×380×250	60
30W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	380×315×290	40
50W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	380×375×340	20
70W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	430×230×440	10
100W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	430×275×260	10
150W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	430×315×290	10
200W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	480×380×345	10
300W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	90m/w	490×275×375	10

F802



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/cdn
10W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80m/w	435×200×225	60
20W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80m/w	350×260×270	40
30W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80m/w	380×365×280	40
50W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80m/w	415×380×330	40
70W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80m/w	380×230×440	20
100W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80m/w	415×280×245	10
200W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80m/w	415×325×285	10
300W	AC185-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80m/w	415×385×340	10



F803



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
30W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w		
50W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w		
100W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w		
150W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w		

F804



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
30W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w		
50W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w		
100W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w		
150W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w		

F805



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
30W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	475*300*430	26
50W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	475*300*430	26
100W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	395*310*500	12
150W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	440*330*120	1
200W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	440*330*120	1
300W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	440*330*120	1
400W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	470*330*120	1
500W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	500*330*180	1
600W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	610*330*205	1
700W	AC85-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	680*330*215	1

F806



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
20W	AC100-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	375*320*115	1
30W	AC100-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	480*360*95	1
40W	AC100-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	540*360*95	1
50W	AC100-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	620*360*95	1
60W	AC100-265V	WWW/R/G/B/Y/RGB	Aluminum	IP65	25000	80lm/w	725*360*95	1

F807



Watts	Voltage	Color Temp.	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
50W	AC180-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w		10
100W	AC180-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w		10
200W	AC180-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w		5
300W	AC180-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w		5
400W	AC180-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w		5
500W	AC180-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w		5

F808



Watts	Voltage	Color Temp.	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
50W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	380*370*340	40
100W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	430*275*260	20
150W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	430*310*290	10
200W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	480*380*345	10
300W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	400*270*375	5
400W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	480*380*345	5
500W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	400*270*375	5
600W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	480*380*345	5

F809



Watts	Voltage	Color Temp.	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
300W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	640X178X260	50
500W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	785X178X240	50
1000W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	330X355X845	20
2000W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	340X325X260	10
3000W	AC85-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	385X325X290	10

F810



Watts	Voltage	Color Temp.	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
100W	AC170-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	600*300*195	50
200W	AC170-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	520*300*125	40
300W	AC170-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	510*320*125	30
500W	AC170-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	420*320*155	20
1000W	AC170-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	580*320*215	10
2000W	AC170-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	330*480*245	15
3000W	AC170-265V	WW/R/G/B/Y/R/G/B	Aluminum	IP65	25000	80lm/w	380*480*245	10

F815



Watts	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/dm
10W	RGB	Aluminum	IP65	25000	80lm/w	540*340*130	50
20W	RGB	Aluminum	IP65	25000	80lm/w	540*340*130	50
30W	RGB	Aluminum	IP65	25000	80lm/w	645*350*185	50
50W	RGB	Aluminum	IP65	25000	80lm/w	790*350*225	50

F816



Watts	Voltage	Color Temp	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/dm
10W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		50
20W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		50
30W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		50
50W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		50
100W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		20
150W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		10
200W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		10
300W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
400W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		


F817



Watts	Voltage	Color Temp	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/dm
30W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
50W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
100W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
150W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
200W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
300W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
400W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		

F818

8



Watts	Voltage	Color Temp	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/dm
50W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
100W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
200W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
300W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		
400W	AC165-265V	WWWRG/B/Y/RGB	IP65	25000	80lm/w		


I812


Watts	Voltage	Color Temp	Material	Dimension (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
30W	AC185-265V	3000-6500K	Aluminum	φ300×H180	25000	90lm/w	385×385×385	6
50W	AC185-265V	3000-6500K	Aluminum	φ350×H185	25000	90lm/w	410×410×401	6
75W	AC185-265V	3000-6500K	Aluminum	φ380×H285	25000	90lm/w	445×445×445	6
100W	AC185-265V	3000-6500K	Aluminum	φ400×H285	25000	90lm/w	445×445×445	6
150W	AC185-265V	3000-6500K	Aluminum	φ450×H185	25000	90lm/w	510×510×510	6

I813


Watts	Voltage	Color Temp	Material	Description	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
150W	AC185-265V	3000-6500K	Aluminum	Driver Cover	25000	90lm/w	345×345×420	1
200W	AC185-265V	3000-6500K	Aluminum	Driver Cover	25000	90lm/w	345×345×420	1
300W	AC185-265V	3000-6500K	Aluminum	Driver Cover	25000	90lm/w	420×420×370	1

I815


Watts	Voltage	Color Temp	Material	Dimension (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cdn
60W	AC85-265V	3000-6500K	Aluminum	φ350×H290	25000	90lm/w	485×485×420	6
100W	AC85-265V	3000-6500K	Aluminum	φ450×H290	25000	90lm/w	520×520×430	6
150W	AC85-265V	3000-6500K	Aluminum	φ450×H290	25000	90lm/w	520×520×430	6
200W	AC85-265V	3000-6500K	Aluminum	φ500×H300	25000	90lm/w	580×580×470	6

I816



Watts	Voltage	Color Temp	Life(h)	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/cn
100W	AC100-265V	3000-6500K	25000	IP65	110lm/w	535*430*280	20
150W	AC100-265V	3000-6500K	25000	IP65	110lm/w	515*310*320	12
200W	AC100-265V	3000-6500K	25000	IP65	110lm/w	480*375*385	10

I817A



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
100W	AC180-265V	3000-6500K	Aluminum	IP65	25000	120-130lm/w		4
150W	AC180-265V	3000-6500K	Aluminum	IP65	25000	120-130lm/w		4
200W	AC180-265V	3000-6500K	Aluminum	IP65	25000	120-130lm/w		4
300W	AC180-265V	3000-6500K	Aluminum	IP65	25000	120-130lm/w		1

I817B



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
100W	AC100-265V	3000-6500K	Aluminum	IP65	25000	120-130lm/w	370*370*205	1
150W	AC100-265V	3000-6500K	Aluminum	IP65	25000	120-130lm/w	410*410*210	1
200W	AC100-265V	3000-6500K	Aluminum	IP65	25000	120-130lm/w	480*480*210	1

I818



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/cn
100W	AC180-305V	3000-6500K	Aluminum	IP65	25000	100-110lm/w	510*500*515	5

I819



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
100W	AC110-255V	3000-6500K	Aluminum	IP65	25000	100-110lm/w	520*400*130	1
150W	AC110-255V	3000-6500K	Aluminum	IP65	25000	100-110lm/w	520*400*130	1

I820



Watts	Voltage	Color Temp	Material	Protection grade	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
150W	AC110-255V	3000-6500K	Aluminum	IP65	25000	100-110lm/w		1

F849



Watts	Voltage	Color Temp	Material	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
50W	AC110-255V	3000-6500K	Aluminum	IP65	80lm/w	600*450*425	10
100W	AC110-255V	3000-6500K	Aluminum	IP65	80lm/w	550*350*400	10
150W	AC110-255V	3000-6500K	Aluminum	IP65	80lm/w	640*350*410	10
200W	AC110-255V	3000-6500K	Aluminum	IP65	80lm/w	670*500*440	10

F850



Watts	Voltage	Color Temp	Material	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
30W	AC110-255V	3000-6500K	Aluminum	IP65	90lm/w	530*230*180	1
50W	AC110-255V	3000-6500K	Aluminum	IP65	90lm/w	560*260*90	1
100W	AC110-255V	3000-6500K	Aluminum	IP65	90lm/w	560*260*90	1
150W	AC110-255V	3000-6500K	Aluminum	IP65	90lm/w	680*300*90	1
200W	AC110-255V	3000-6500K	Aluminum	IP65	90lm/w	680*300*90	1

F851




Watts	Voltage	Color Temp	Material	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
50W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	620*325*325	12
100W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	530*360*370	12
150W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	660*365*445	12
200W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	725*510*255	8

F852



Watts	Voltage	Color Temp	Material	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
30W	AC85-265V	3000-6500K	Aluminum	IP65	73lm/w	355*155*75	1
50W	AC85-265V	3000-6500K	Aluminum	IP65	73lm/w	455*205*85	1
100W	AC85-265V	3000-6500K	Aluminum	IP65	73lm/w	670*260*75	1
150W	AC85-265V	3000-6500K	Aluminum	IP65	73lm/w	820*325*95	1
200W	AC85-265V	3000-6500K	Aluminum	IP65	73lm/w	970*360*115	1

F853



Watts	Voltage	Color Temp	Material	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
100W	AC130-265V	3000-6500K	Aluminum	IP65	100lm/w		1
150W	AC130-265V	3000-6500K	Aluminum	IP65	100lm/w	630*295*115	1
200W	AC130-265V	3000-6500K	Aluminum	IP65	100lm/w	730*355*140	1

F855



Watts	Voltage	Color Temp	Material	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
50W	AC85-265V	3000-6500K	Aluminum	IP65	95lm/w	480*185*100	1
100W	AC85-265V	3000-6500K	Aluminum	IP65	95lm/w	590*222*110	1
150W	AC85-265V	3000-6500K	Aluminum	IP65	95lm/w	718*275*110	1

F856



Watts	Voltage	Color Temp	Material	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
30W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w		20
50W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	415*415*345	15
100W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	475*375*310	10
200W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	545*415*385	10
300W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	625*430*410	10

F857




Watts	Voltage	Color Temp	Material	Protection grade	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
30W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w		20
50W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	415*415*345	15
100W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	475*375*310	10
200W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	545*415*385	10
300W	AC180-265V	3000-6500K	Aluminum	IP65	110lm/w	625*430*410	10

LED TUBE&FIXTURE SERIES




T600




Watts	Voltage	Color Temp	Length(M)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
8W	AC220-240V	3000-6500K	0.6	25000	85-90lm/w	640*228*170	30 with EPE
18W	AC220-240V	3000-6500K	1.2	25000	85-90lm/w	1240*228*170	30 with EPE
8W	AC100-265V	3000-6500K	0.6	25000	85-90lm/w	640*228*170	30 with EPE
18W	AC100-265V	3000-6500K	1.2	25000	85-90lm/w	1240*228*170	30 with EPE

T601



Watts	Voltage	Color Temp	Length(M)	Life(h)	Lighting Effect	Packing Size (mm)	Packing position
9W	AC165-265V	3000-6500K	0.6	25000	90lm/w	640*220*170	30 with EPE
18W	AC165-265V	3000-6500K	1.2	25000	90lm/w	1240*220*170	30 with EPE
25W	AC165-265V	3000-6500K	1.2	25000	90lm/w	1240*220*170	30 with EPE
30W	AC165-265V	3000-6500K	1.2	25000	90lm/w	1240*220*170	30 with EPE

T602



Watts	Voltage	Color Temp	Length(M)	Life(h)	Lighting Effect	Packing Size (mm)	Packing position
9W	AC165-265V	3000-6500K	0.6	25000	90lm/w	640*220*170	30 with EPE
18W	AC165-265V	3000-6500K	1.2	25000	90lm/w	1240*220*170	30 with EPE

T603




Watts	Voltage	Color Temp	Length(M)	Life(h)	Lighting Effect	Packing Size (mm)	Packing position
10W	DC12-60V	3000-6500K	0.6	25000	90lm/w	640*220*170	30 with EPE
20W	DC24-80V	3000-6500K	1.2	25000	90lm/w	1240*220*170	30 with EPE

T604



Watts	Voltage	Color Temp	Length(M)	Life(h)	Lighting Effect	Packing Size (mm)	Packing position
9W	AC165-265V	WWWW/GB	0.6	25000	90lm/w	650*230*180	30 with EPE
18W	AC165-265V	WWWW/GB	1.2	25000	90lm/w	1240*230*180	30 with EPE

T605



Watts	Voltage	Color Temp	Length(M)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
9W	AC185-265V	3000-6500K	0.3	25000	90lm/w	650*230*195	30 with EPE
18W	AC185-265V	3000-6500K	1.2	25000	90lm/w	1240*195*125	30 with EPE

T606



Watts	Voltage	Color Temp	Length(M)	Life(h)	Packing Size (mm)	Packing pcs/ctn
6W	DC12V	3000-6500K	0.3	25000	350*250*145	30
12W	DC12V	3000-6500K	0.6	25000	650*250*145	30
18W	DC12V	3000-6500K	1.2	25000	930*250*145	30

T608



Watts	Voltage	Color Temp	Length(M)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pcs/ctn
4W	AC185-265V	3000-6500K	0.3	25000	100lm/w	350*250*145	30
8W	AC185-265V	3000-6500K	0.6	25000	100lm/w	625*250*145	30
12W	AC185-265V	3000-6500K	0.9	25000	100lm/w	800*250*145	30
18W	AC185-265V	3000-6500K	1.2	25000	100lm/w	1220*250*145	30

T630



Type	Voltage	Thickness (MM)	Packing Size (mm)	Packing pcs/ctn
0.6M FOR LED TUBE 1*9W	AC85-265V	0.2	650*195*125	30
1.2M FOR LED TUBE 1*18W	AC85-265V	0.2	1240*195*125	30
0.6M FOR LED TUBE 1*9W	AC85-265V	0.25	650*195*125	30
1.2M FOR LED TUBE 1*18W	AC85-265V	0.25	1240*195*125	30
0.6M FOR LED TUBE 2*9W	AC85-265V	0.2	1535*195*105	30
1.2M FOR LED TUBE 2*18W	AC85-265V	0.2	1240*195*125	30
0.6M FOR LED TUBE 2*9W	AC85-265V	0.25	650*195*125	30
1.2M FOR LED TUBE 2*18W	AC85-265V	0.25	1535*195*105	30



T631




Watts	Voltage	Thickness (MM)	Packing Size (mm)	Packing pos/ctn
0.8M FOR LED TUBE 1*9W	AC85-265V	0.2	650*185*125	36
1.2M FOR LED TUBE 1*18W	AC85-265V	0.2	1240*185*125	36
0.8M FOR LED TUBE 1*9W	AC85-265V	0.25	650*185*125	36
1.2M FOR LED TUBE 1*18W	AC85-265V	0.25	1240*185*125	36
0.8M FOR LED TUBE 2*9W	AC85-265V	0.2	1535*185*135	36
1.2M FOR LED TUBE 2*18W	AC85-265V	0.2	1240*185*125	36
0.8M FOR LED TUBE 2*9W	AC85-265V	0.25	650*185*125	36
1.2M FOR LED TUBE 2*18W	AC85-265V	0.25	1535*185*135	36

T632A




Watts	Voltage	Color Temp	Thickness (MM)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/ctn
9W	AC85-265V	3000-6500K	0.3	25000	70lm/w	325*290*180	20
18W	AC85-265V	3000-6500K	0.6	25000	70lm/w	625*290*180	20
24W	AC85-265V	3000-6500K	0.9	25000	70lm/w	930*290*180	20
36W	AC85-265V	3000-6500K	1.2	25000	70lm/w	1240*290*180	20
44W	AC85-265V	3000-6500K	1.5	25000	70lm/w	1535*290*180	20

T632B



Watts	Voltage	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/ctn
T12-1.2M-A5 54W	AC85-265V	3000-6500K	25000	70lm/w		
T24-1.2M-A5 72W	AC85-265V	3000-6500K	25000	70lm/w		
T24-1.2M-A5 72W	AC85-265V	3000-6500K	25000	70lm/w		
T24-1.2M-A5 120W	AC85-265V	3000-6500K	25000	70lm/w		
Fu8 T8-2.4M-A2 36W	AC85-265V	3000-6500K	25000	70lm/w		
T12-1.2M-A5 36W	AC85-265V	3000-6500K	25000	70lm/w		

T632C




Watts	Voltage	Color Temp	Thickness (MM)	Life(h)	Lighting Effect	Packing Size (mm)	Packing pos/ctn
20W	AC85-265V	3000-6500K	0.6	25000	73lm/w	640*410*175	36
40W	AC85-265V	3000-6500K	1.2	25000	73lm/w	1240*410*175	36

T633



Watts	Voltage	Color Temp	Dimension (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing position
18W	AC85-265V	3000-6500K	600*48*30	25000	65-72m/w	680*290*225	30
28W	AC85-265V	3000-6500K	900*48*30	25000	65-72m/w	960*290*225	30
36W	AC85-265V	3000-6500K	1200*48*30	25000	65-72m/w	1260*290*225	30
42W	AC85-265V	3000-6500K	900*75*26	25000	65-72m/w	930*270*170	20
45W	AC85-265V	3000-6500K	600*105*26	25000	65-72m/w	630*270*210	20
60W	AC85-265V	3000-6500K	1200*76*26	25000	65-72m/w	1230*270*170	20
70W	AC85-265V	3000-6500K	900*105*26	25000	65-72m/w	930*270*210	20
90W	AC85-265V	3000-6500K	1200*130*26	25000	65-72m/w	1230*270*210	20

T650




Watts	Voltage	Color Temp	Dimension (mm)	Life(h)	Lighting Effect	Packing Size (mm)	Packing position
18W	AC85-265V	3000-6500K	600*54*49	25000	80m/w	660*290*225	10
28W	AC85-265V	3000-6500K	900*54*49	25000	80m/w	960*290*225	10
36W	AC85-265V	3000-6500K	1200*54*49	25000	80m/w	1260*290*225	10
45W	AC85-265V	3000-6500K	1000*54*49	25000	80m/w	1060*290*225	10

T651



Type	Voltage	Packing Size (mm)	Packing position
0.6M FOR LED TUBE 1X9W	AC85-265V	690*280*210	8
0.6M FOR LED TUBE 2X9W	AC85-265V	690*290*290	8
1.2M FOR LED TUBE 1X18W	AC85-265V	1290*280*210	8
1.2M FOR LED TUBE 2X18W	AC85-265V	1290*280*210	8
1.5M FOR LED TUBE 1X28W	AC85-265V	1580*280*210	8
1.5M FOR LED TUBE 2X28W	AC85-265V	1580*280*190	4

T652




Watts	Voltage	Dimension (mm)	Color Temp	Life(h)	Lighting Effect	Packing Size (mm)	Packing position
1*9W 0.6M	AC165-265V	607*59*85	3000-6500K	25000	80m/w	630*290*225	12
1*18W 1.2M	AC165-265V	1225*59*85	3000-6500K	25000	80m/w	1230*290*220	12
2*9W 0.6M	AC165-265V	607*100*85	3000-6500K	25000	80m/w	630*290*230	8
2*9W 1.2M	AC165-265V	1225*100*85	3000-6500K	25000	80m/w	1230*290*230	8

T653




Watts	Voltage	Color Temp	Body	Packing Size (mm)	Packing pcs/cdn
18W	220V	3000/4000/5000K	White/Black		30
24W	220V	3000/4000/5000K	White/Black		30


T654



Meters	Lamp PCS	Body	Packing Size (mm)	Packing pcs/cdn
1M	2-4	White/Black		20
1.5M	3-5	White/Black		20
2M	4-6	White/Black		20



LSL01



Voltage	Color Temp	Protection grade	Packing Size (mm)	Packing pcs/cdn
12V 2835	WWWW	IP65		50
12V 2835	RED/GREEN/PINK/CAMBER/IC7 BLUE/LEMON			50
Connector wire				50



LSL02



Voltage	Color Temp	Protection grade	Packing Size (mm)	Packing pcs/ctn
12V 2835-60	W/W/B	IP20	380*290*200	200
12V 2835-60	R/G/Y	IP25	380*290*200	200
12V 2835-60	W/W/B	IP44	380*290*200	200
12V 2835-60	R/G/Y	IP44	380*290*200	200
12V 2835-120	W/W/B	IP25	380*290*200	200
12V 2835-120	R/G/Y	IP20	380*290*200	200
12V 5050-60	RGB	IP25	380*290*200	200
12V 5050-60	RGB	IP44	380*290*200	200

LSL03



Voltage	Color Temp	Specification	Packing Size (mm)	Packing pcs/ctn
12V 5050-60	RGB	5MholUmet.12V 3A	580*395*230	20
12V 2835-64	RGB	5MholUmet.12V 3A	580*395*230	20

LSL04



Voltage	Color Temp	Protection grade	Packing Size (mm)	Packing pcs/ctn
220V COB	W/W/W	IP65	330*330*200	1000
220V 2835-120-6MM FPC	W/W/W/B	IP65	330*330*200	1000
220V 2835-120-6MM FPC	R/G/Y/PK	IP65	330*330*200	1000
220V 2835-180-6MM FPC	W/W/W/B	IP65	330*330*200	1000
220V 2835-180-6MM FPC	R/G/Y/PK	IP65	330*330*200	1000
220V 2835-180-10MM FPC	W/W/W/B	IP65	330*330*200	1000
220V 2835-180-10MM FPC	R/G/Y/PK	IP65	330*330*200	1000

LSL05



Voltage	Rated Current	Color	Packing Size (mm)	Packing pcs/ctn
220V	6A	SINGLE COLOR	450*280*250	50



Voltage	Color Temp	Control Mode	Packing Size (mm)	Packing pcs/ch
220V	RGB	POWER CHANGABLE + REMOTE	445*415*255	50

LSL07



Voltage	Watts	Operating Temperature	Packing Size (mm)	Packing pcs/ch
12V	2W	-30C°-65C°		
12V	6W	-30C°-65C°		
12V	200W	-30C°-65C°		
12V	36W	-30C°-65C°		
12V	120W	-30C°-65C°		
12V	360W	-30C°-65C°		



MOSQUITO LAMP SERIES

NECO-816 2x10W

Tubes: 2x10W
Coverage Area: 60m²
Power: 32Watts
Unit Dim.: 41x10x31.5cm
Carton Dim.: 505x425x550/12pcs

NECO-816 2x15W

Tubes: 2x15W
Coverage Area: 80m²
Power: 40Watts
Unit Dim.: 51x10x31.5cm
Carton Dim.: 505x425x550/10pcs

NECO-816 2x20W

Tubes: 2x20W
Coverage Area: 100m²
Power: 40Watts
Unit Dim.: 66x10x31.5cm
Carton Dim.: 660x330x550/10pcs

NECO-817

Tubes: 2x2W
Carton Dim.: 515x320x480/10pcs
Tubes: 2x3W
Carton Dim.: 515x407x480/10pcs
Tubes: 2x4W
Carton Dim.: 512x385x480/12pcs
Tubes: 2x5W
Carton Dim.: 587x385x480/12pcs

PVC&BOX SERIES

LOOPING BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	420×285×345	240
25	WHITE/BLACK	420×285×345	240

THREE WAY BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	490×345×345	240
25	WHITE/BLACK	490×345×345	240

PVC FADAPTER



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	430×340×315	1200
25	WHITE/BLACK	450×360×315	1200

ONE WAY BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	455×345×345	240
25	WHITE/BLACK	455×345×345	240

TWO WAY ANGLE BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	455×345×345	240
25	WHITE/BLACK	455×345×345	240

PVC SADDLE CLIP



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	500×330×380	1800
25	WHITE/BLACK	500×330×380	1800

TWO WAY BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	450×330×345	240
25	WHITE/BLACK	450×330×345	240

4 WAY BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	455×345×345	240
25	WHITE/BLACK	455×345×345	240

UNFINISHED BOXES



Specification (mm)	Thickness (mm)	Size Of Cn (mm)	Pack/ctn
34×35	0.7	365×332×193	100
34×35	0.7	730×332×193	50

FOUR WAY BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	520×345×345	240
25	WHITE/BLACK	520×345×345	240

5 WAY BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
20	WHITE/BLACK	565×345×345	240
25	WHITE/BLACK	565×345×345	240

PVC BOX



Specification (mm)	Color	Size Of Cn (mm)	Pack/ctn
34×35×0.7	WHITE	245×165×190	400
24×35×0.7	WHITE	485×335×380	400

FAN



MINI CHARGING FAN
3.7V 7.2AH



8" CHARGING FAN
3.7V 1200MAH*4
3.7V 1800MAH*4



16" CHARGING FAN
18" CHARGING FAN
11.1V 4AH



8" CHARGING FAN
(WITH TRIPOD STAND)
3.7V 1800MAH*4

SWITCH&SOCKET



1 GANG SWITCHED WITH MULTI
SOCKET WITH NEON



15A 1 GANG SWITCHED SOCKET
WITH NEON



13A 1 GANG SWITCHED SOCKET
WITH NEON



1 GANG SWITCHED WITH SPIN
MULTI SOCKET WITH NEON



1 GANG SWITCHED WITH MULTI
SOCKET WITH NEON & USB



1G 1W SWITCH



2G 1W SWITCH



3G 1W SWITCH



20A/25A/32A SWITCH WITH NEON



1G 1W SWITCH



2G 1W SWITCH



3G 1W SWITCH



13A 2 GANG SWITCHED SOCKET WITH NEON



13A 2 GANG SWITCHED WITH MULTI
SOCKET WITH NEON



13A 2 GANG SWITCHED WITH MULTI
SOCKET WITH NEON & USB